9/25/2018

Supplier	McMaster- Carr Supply	\$21.36 McMaster- Carr Supply	\$96.43 McMaster- Carr Supply Co,	\$6.10 McMaster- Carr Supply	\$11.30 McMaster- Carr Supply Co,	McMaster- Carr Supply Co,	\$72.22 McMaster- Carr Supply	McMaster- Carr Supply	McMaster- Carr Supply Co,
Total	\$75.40 M	\$21.36	\$96.43 N	\$6.10 \S\ \O\ \O\ \O\ \O\ \O\ \O\ \O\ \O\ \O\	\$11.30 \(\overline{\overli	\$38.04 M	\$72.22 M	\$423.79 McMaster Carr Supply	\$74.32 McMaster- Carr Supply Co,
Past								69	
Aging F	0	0	0	0	0	0	0	0	0
Price/Unit Aging	\$ 3.77 / Ea	\$ 3.56 / pcs	\$ 96.43 / Ea	\$ 0.06 / Ea	\$ 0.23 / Ea	\$ 6.34 / Ea	\$ 6.02 / ft	\$ 195.30 / ft	\$ 24.77 / ft
Receive Date	9/25/2018	9/25/2018	9/25/2018	9/25/2018	9/25/2018	9/25/2018	9/25/2018	9/25/2018	9/25/2018 \$ 24.77 / ft
Status	Stock	Stock	Stock	Stock 9	Stock	Stock	Stock 9	Stock 9	Stock 9/
Container No	S113446	S113453	S113451	S113448	S113463	S113458	S113456	S113467	S113468
Received Accounting Quantity Job No		1	7.						
Received A	20	9	-	100	20	9	12	N	г.
Due	9/26/2018								
Order		9	-	100	20	9	12	2	т
For Project Equipment Order No									
Project									
For Part No									
Description	Steel Spring Plunger 3/8""-16 x 5/8"" Long receive ea	Plastic Handle 1/4""-20 x 1/2" Depth x 3-7/8"" Long	Dial Indicator with Certificate 0"" to 1.000"". Range X 0.001"". Increments	Steel Phillips Flat Head Screw #10-32 x 3/8"" Long receive ea	Steel RoundHead Screw 1/4-28 x 1-1/2*** Long receive ea	SS Knurled- Head Thumb Screw 6-32 Thread Size x 1/2" Long	Extension Spring, SS, 20"" Long x 0.25"" OD x 0.02" Dia.	Bearing Bronze Rod 2.250***	Brass C360 Round Bar 1.000"" : MATERIAL:C360 BRASS ASTM B16
Purchased Item	3126A149	57455K710	8662A61	90273A827	90276A563	93585A015	9665K57	.250	MT-BRASS- 10360-R1.000
Terms	1 2% 10 Net 30					<i>31</i>	ai .	<	20
No No	-	2	m	4	ις.	9			
r Item No							7	00	0
Supplier Item No	P0041115 MCM001-								
PO No	P0041115								

2/2
n_Key={FF1CA5E7-BE36-4027-BA1F-E42BF42C0CE1}&Session_Key 2/2
Sessio
Opener
2.asp?(
iewer
https://www.plexonline.com/FF1CA5E7-BE36-4027-BA1F-E42BF42C0CE1/Plexus_Control/Report_Vir

Print

9/25/2018

Plex 9/25/2018 12:43 PM dart. Tollis. Andrew



Dart Aerospace Ltd. 1270 Aberdeen St Hawkesbury, ON K6A 1K7 Canada

Tel (613) 632-5200

### PURCHASE ORDER PO041115

Supplier:

MCM001-VU

McMaster-Carr Supply Co,

P.O. Box 7690

Chicago, IL 60680-7690 USA

Phone: 330 995 5500 Fax: 330 995 9600

Ship To: 1270 Aberdeen Street

Hawkesbury

ON

K6A 1K7 Canada Phone: 613-632-5200 PO No:

PO041115

PO Date:

9/24/18 9/26/18

Due Date: Purchase Order

Revision:

Revision Date:

Ship-To Contact:

Lavoie, ChantalPhone:

clavoie@dartaero.com

Via:

Ground

**Pymt Terms:** 

2% 10 Net 30

Freight Terms:

Special Comments:

Line			Supplier				Due	Order	Deseived		10-14	Fredam et a
Item	Job	Part	Part No	Description	Status	Account	Date	Quantity	Received Quantity	Balance	Unit Price (USD)	Extended Price
(1)		3126A149	3126A92 1/pk	Steel Spring Plunger 3/8"-16 x 5/8" Long receive ea	Firmed	- 20)	9/26/18	20 Ea SEP 2 5	2018 / C	20 Ea	\$3.77/Ea	\$75.40
(2)		57455K710	1/pk	Plastic Handle 1/4"-20 x 1/2" Depth x 3-7/8" Long	Firmed		9/26/18 SEP 2 !		0 pcs	6 pcs	\$3.56/pcs	\$21.36
(3)		8662A61	1/pk	Dial Indicator with Certificate 0" to 1.000" Range X 0.001" Increments receive ea	Firmed		9/26/18 SEP 2 5	1 Ea	0 Ea	1 Ea	\$96.43/Ea	\$96.43
(4)		90273A827	1	Steel Phillips Flat Head Screw #10-32 x 3/8" Long receive ea	Firmed		9/26/18 EP 2 5	100 Ea 2018 10	0 Ea	100 Ea	\$0.061/Ea	\$6.10
<u>(5)</u>		90276A563		Steel RoundHead Screw 1/4-28 x 1-1/2" Long receive ea	Firmed  O   Y	SEP 2	9/26/18	50 Ea	0 Ea	50 Ea	\$0.226/Ea	\$11.30
6		93585A015		SS Knurled- Head Thumb Screw 6-32 Thread Size x 1/2" Long	Firmed		9/26/18 SEP 2 !	6 Ea	O Ea	6 Ea	\$6.34/Ea	\$38.04
7 . A.		9665K57	,	Extension Spring, SS, 20" Long x 0.25" OD x 0.02" Dia.	Firmed	- 11	9/26/18 SEP	12 ft 2 5 2018	Oft	12 ft	\$6.0182407/ft	\$72.22



Dart Aerospace Ltd. 1270 Aberdeen St Hawkesbury, ON K6A 1K7 Canada

### **PURCHASE ORDER** PO041115

Tel (613) 632-5200

					Ite	ms						
Line Item	Job	Part	Supplier Part No	Description	Status	Account	Due Date	Order Quantity	Received Quantity	Balance	Unit Price (USD)	Extended Price
8		MBRASSR2.250	8932K54 6.5 inch <sup>*</sup> long	Bearing Bronze Rod 2.250"	Firmed 2.		9/26/18 SEP 2	2.167 ft 2 5 2018	0 ft	2 ft	\$195.29629/ft	\$423.21
Line Item Note	4 pc	s of 6.5" = 2.1666	5 ft								1,	-
9		MT-BRASS- C360-R1.000	8953K98 3ft	Brass C360 Round Bar 1.000" : MATERIAL:C360 BRASS ASTM B16	Firmed	-	9/26/18	3 ft	3 I +	3 ft	\$24.7733/ft M 18/04	*******
(10)		MT-BRASS- C360-R1.250	3ft	Brass C360 Round Bar 1.250" : MATERIAL:C360 BRASS ASTM B16	Firmed	•	9/26/18	3 ft	3.ft	3 ft	\$36.69/M AT 18/09	
11		97524A032		Sealing Blind Rivet	Firmed	- 500	9/26/18 S	500 Ea	(	500 Ea	\$0.0982/Ea	\$49.10
					C				4 2	/	Grand Total:	\$977.55

#### **Order Notes**

**Procurement Quality Clauses** 

A005 RIGHT OF ENTRY

A016 PERSONNEL QUALIFICATION

A026 CERTIFICATION OF MATERIAL CONFORMANCE

A032 DOCUMENT SPECIAL REQUIREMENTS

A033 STATEMENT OF CONFORMITY/TEST RECORDS FOR NAS, AN and MS FASTENERS

A040 NOTIFICATION OF QUALITY ESCAPE

A041 QUALITY MANAGEMENT SYSTEM

A042 DART NOTIFICATION BY SUPPLIER

A043 RETENTION OF QUALITY DOCUMENTS

A048 COUNTERFEIT PARTS AVOIDANCE, DETECTION, MITIGATION AND DISPOSITION PROGRAM

A049 SUPPLIER AWARENESS

Terms & Condition of Purchasing(Suppliers) and Procurement Quality Clauses are an integral part of our AS9100 requirements. To learn in detail, please visit www.dartaerospace.com for further explanation.

Plex 9/24/18 11:44 AM dart.lavoie.chantal



Packing List

200 Aurora Industrial Pkwy Aurora OH 44202-8087 330-995-5500 cle.sales@mcmaster.com Dart Aerospace Ltd 1270 Aberdeen St Hawkesbury ON K6A 1K7 Canada Purchase Order PO041115

Order Placed By Chantal Lavoie

McMaster-Carr Number 1619001-01 Page 1 of 1 09/24/2018

	1619001-01		
Line	Product	Ordered	Shipped
3126A149	Slotted Long-Nose Steel Spring Plunger, Zinc-Plated, 3/8"-16 Thread, 4.5 & 18.5 lb. Force, without Locker	20 Each	
57455K71	Plastic Tapered Handle, High-Temperature, with 1/4"-20 Size 1/2" Deep Thread, 3-7/8" Long	6 Each	
8662A61	Combination Dial Plunger-Style Variance Indicator with NIST Certificate & 0" to 1" Measuring Range	1 Each	1 🗸
90273A827	Steel Phillips Flat Head Screw, 82 Degree Countersink Angle, 10-32 Thread Size, 3/8" Long, Packs of 100	1 Pack	1/
90276A563	Steel Decorative Round Head Slotted Screws, 1/4"-28 Thread Size, 1-1/2" Long, Packs 50	of 1 Pack	1
93585A015	Stainless Steel High-Profile Knurled-Head Thumb Screw, 6-32 Thread Size, 1/2" Long	6 Each	6
9665K57	Corrosion-Resistant Extension Spring Stock, 20" Long, 0.25" OD, 0.020" Wire Diameter, Sold In 20" Lengths. Sending 8 Pieces To Meet Your Need For 12FT	8 Each	8
8932K54	Oil-Filled 841 Bearing Bronze Rod, 2-1/4" Diameter, 6-1/2" Long, Sold In 6-1/2" Pieces. Sending 4 Pieces To Meet Yo Ur Need For 2FT	4 Each	4/
97524A032	Sealing Blind Rivets, Aluminum, Domed Head, with Aluminum Mandrel, 1/8" Diameter, 0.425" Long, Packs of 100	5 Packs	5



200 Aurora Industrial Pkwy Aurora OH 44202-8087 330-995-5500 cle.sales@mcmaster.com

8953K98

8953K29

Line

Dart Aerospace Ltd 1270 Aberdeen St Hawkesbury ON K6A 1K7 Canada

## **Packing List**

Purchase Order PO041115

Order Placed By Chantal Lavoie

McMaster-Carr Number 1619001-02

Page 1 of 1 09/24/2018

Product	Ordered	Shipped
Ultra-Machinable 360 Brass Rod, 1" Diameter, 3 Feet Long	1 Each	(1)
Ultra-Machinable 360 Brass Rod, 1-1/4" Diameter, 3 Feet Long	1 Each	1

## McMASTER-CARR.

# Ultra-Machinable 360 Brass Rod

\$74.32 Each 8953K98



Material	360 Brass
Cross Section Shape	Round
Construction	Solid
Appearance	Plain
Diameter	1 <sup>n</sup>
Diameter Tolerance Range	-0.003" to 0.003"
Tolerance Rating	Standard
Yield Strength	15,000 psi
Fabrication	Cold Worked
Temper	H02
Temper Rating	1/2 Hard
Hardness	Rockwell B25 (Soft)
Heat Treatable	No
Specifications Met	ASTM B16
Density	0.307 lbs./cu. in.
Surface Resistivity	39.9 Ohms
Melting Point Temperature	1630° F
Modulus of Elasticity	$14.0 \text{ ksi} \times 10^3$
Thermal Conductivity	67 Btu/hrft°F @ 68° F
Elongation	25%
Material Composition	
Copper	60-63%
Iron	0-0.35%
Lead	2.5-3.7%
Silicon	0-0.17%
Zinc	32.95-37.15%
Length Tolerance Range	-0.5" to 0.5"
Length	3 ft.
RoHS	Not Compliant

+30+

With the highest lead content of all the brass alloys, 360 offers the best machinability. Often called free-machining and free-cutting brass, it stands up to high-speed drilling, milling, and tapping operations with minimal wear on your tools. It's commonly used for gears, pinions, and lock components.

APPROVED | August | A WW BRASS C360 ROUND BAR BY MT-BRASS-C360-R VIA DART 17.11.22 DATE 17-732 ECN# TOLERANCES PER MANUFACTURER SPECIFICATIONS DESCRIPTION NEW ISSUE WHERE D.DDD IS DIAMETER IN INCHES SPECIFICATION CONTROL DRAWING MT-BRASS-C360-R-[D.DDD] MT-BRASS-C360-R-0,250 REV. C360 BRASS ASTM B16 PURCHASE MATERIAL: SPECIFICATION: PART NUMBER: **EXAMPLE**: 00

0

۵

0

### MATERIAL RECEIPT INSPECTION FORM

MATERIAL: <u>MT-6</u> DATE: <u>18/09/</u>	го		PO / BATCH	NO.: <u>P0041</u>	415/5/13468					
MATERIAL CERT REC'D:	THICKNESS ORDERED: 1.000 "									
QUANTITY RECEIVED: 3 ft							VED: 1.000	K		
QUANTITY INSPECTED: 3 ft					SHEE	T SIZE ORDE	RED:			
QUANTITY REJECTED:					SHEET	SIZE RECEI	VED:			
DESCRIPTION		CR								
DESCRIPTION		eck N)				COMMEN.	TS			
SURFACE DAMAGE	Y	0								
CORRECT FINISH	(Y)	N								
CORROSION	Y	(1)								
CORRECT GRAIN DIRECTION	(Y)	N								
CORRECT MATERIAL PER M-DRAWING	(Y)	N	ASTM	B16						
CORRECT THICKNESS	(Y)	N								
PHOTO REQUIRED	Y	(N)								
CORRECT REF # TO LINK CERT	0	N	1004/11	5						
CORRECT MATERIAL IDENTFICATION		N	1 -0 1777	-						
CORRECT M# ON THE MATERIAL	N	N								
DOES THIS MATERIAL REQUIRE										
ENGINEERING SIGN OFF	Υ	M								
DOES THIS REQUIRE AN EXTRUSION REPORT	Υ	3					-			
CUT SAMPLE PIECE		-0	TERIAL AN	D PRE	ORM	A HARDNE	SS CHECK			
			ORD RESU				oo on Loru			
			HRC	HRB		DUR A	DUR D	WEBSTER		
TYPE OF MATERIAL										
SIZE OF TEST SAMPLE										
HARDNESS / DUROMETER READIN	VG									
	<u>te</u>	sters	located in th	e Quality	Office					
C 18 INSPECTION		-				ENGINEER	ING SIGNOF	F (if required)		
INSPECTED BY:					SIGNED OFF BY:					
DATE: 18/09/25					DATE:					

Attach this inspection sheet with the corresponding material cert and remit to be scanned and received in

## McMASTER-CARR.

## Ultra-Machinable 360 Brass Rod

\$110.07 Each 8953K29



Material	360 Brass
Cross Section Shape	Round
Construction	Solid
Appearance	Plain
Diameter	1 1/4"
Diameter Tolerance Range	-0.003" to 0.003"
Tolerance Rating	Standard
Yield Strength	15,000 psi
Fabrication	Cold Worked
Temper	H02
Temper Rating	1/2 Hard
Hardness	Rockwell B25 (Soft)
Heat Treatable	No
Specifications Met	ASTM B16
Density	0.307 lbs./cu. in.
Surface Resistivity	39.9 Ohms
Melting Point Temperature	1630° F
Modulus of Elasticity	$14.0 \text{ ksi} \times 10^3$
Thermal Conductivity	67 Btu/hrft°F @ 68° F
Elongation	25%
Material Composition	
Copper	60-63%
Iron	0-0.35%
Lead	2.5-3.7%
Silicon	0-0.17%
Zinc	32.95-37.15%
Length Tolerance Range	-0.5" to 0.5"
Length	3 ft.
RoHS	Not Compliant

+3. H

With the highest lead content of all the brass alloys, 360 offers the best machinability. Often called free-machining and free-cutting brass, it stands up to high-speed drilling, milling, and tapping operations with minimal wear on your tools. It's commonly used for gears, pinions, and lock components.

BY APPROVED WW BRASS C360 ROUND BAR NA MT-BRASS-C360-R DATE 17.11.22 ECN# 17-732 7 TOLERANCES PER MANUFACTURER SPECIFICATIONS DESCRIPTION NEW ISSUE WHERE D.DDD IS DIAMETER IN INCHES SPECIFICATION CONTROL DRAWING MT-BRASS-C360-R-[D.DDD] MT-BRASS-C360-R-0.250 REV. C360 BRASS PURCHASE MATERIAL: SPECIFICATION: PART NUMBER: **EXAMPLE**: 60

۵

O

### MATERIAL RECEIPT INSPECTION FORM

TYPE OF MATERIAL  SIZE OF TEST SAMPLE  HARDNESS / DUROMETER READING  testers located in the Quality Office	MATERIAL: M7-	250		PO / BATCH	NO .: POO4	1115/5/1346			
QUANTITY RECEIVED: 31/1 SHEET SIZE ORDERED: SHEET SIZE ORDERED: SHEET SIZE RECEIVED: SHEET SI	DATE: 18/09	/25	5						
QUANTITY INSPECTED:  QUANTITY REJECTED:  DESCRIPTION  NCR (Check Y/N)  SURFACE DAMAGE Y (N)  CORRECT FINISH CORRECT FINISH CORRECT GRAIN DIRECTION  CORRECT GRAIN DIRECTION  CORRECT THICKNESS PHOTO REQUIRED  CORRECT REF # TO LINK CERT CORRECT MATERIAL REQUIRE ENGINEERING SIGN OFF Y (N)  CORRECT MATERIAL REQUIRE ENGINEERING SIGN OFF Y (N)  CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK.  RECORD RESULTS BELOW  HRC HRB DUR A DUR D WEBSTI						THIC	KNESS ORDE	RED: /.25	so "
QUANTITY INSPECTED:  QUANTITY REJECTED:  DESCRIPTION  NCR (Check Y/N)  SURFACE DAMAGE Y   (N)  CORRECT FINISH CORRECT FINISH CORRECT GRAIN DIRECTION  CORRECT GRAIN DIRECTION  CORRECT THICKNESS PHOTO REQUIRED  CORRECT REF # TO LINK CERT CORRECT MATERIAL REQUIRE ENGINEERING SIGN OFF Y   (N)  CORRECT MATERIAL REQUIRE ENGINEERING SIGN OFF Y   (N)  CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK.  RECORD RESULTS BELOW  HRC HRB DUR A DUR	QUANTITY RECEIVED: 3\$+								
DESCRIPTION  OUANTITY REJECTED:  DESCRIPTION  OUR (Check YNN)  SURFACE DAMAGE  CORRECT FINISH  CORRECT FINISH  CORRECT GRAIN DIRECTION  CORRECT GRAIN DIRECTION  CORRECT HICKNESS  V N PHOTO REQUIRED  CORRECT HICKNESS  V N PHOTO REQUIRED  CORRECT MATERIAL IDENTFICATION  OUR CORRECT MATERIAL IDENTFICATION  CORRECT MATERIAL IDENTFICATION  CORRECT MATERIAL REQUIRE  ENGINEERING SIGN OFF  V N DOES THIS MATERIAL REQUIRE  ENGINEERING SIGN OFF  V N  CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK.  RECORD RESULTS BELOW  HRC  HRC  HRB  DUR A  DUR D  WEBSTI  STEET SIZE RECEIVED:   COMMENTS  COMMENTS  COMMENTS  COMMENTS  V N  CORRECT FINISH  CORRECT FINISH  CORRECT FINISH  CORRECT MATERIAL  CORRECT MATERIAL  TO LINE									1.030
DESCRIPTION  OCAPECT FOR A COMMENTS  SURFACE DAMAGE Y (N)  CORRECT FINISH CORROSION Y (N)  CORRECT GRAIN DIRECTION  CORRECT MATERIAL PER M-DRAWING CORRECT THICKNESS Y N  PHOTO REQUIRED CORRECT THICKNESS Y N  PHOTO REQUIRED CORRECT MATERIAL IDENTFICATION N  CORRECT MATERIAL IDENTFICATION N  CORRECT MATERIAL REQUIRE ENGINEERING SIGN OFF Y (N)  CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK.  RECORD RESULTS BELOW  HRC HRB DUR A DUR D WEBSTI  SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  Lesters located in the Quality Office									
DESCRIPTION  (Check Y/N)  SURFACE DAMAGE Y (N)  CORRECT FINISH Y N  CORROSION Y (N)  CORRECT GRAIN DIRECTION N  CORRECT MATERIAL PER M-DRAWING (N) N  CORRECT THICKNESS N N  PHOTO REQUIRED Y (N)  CORRECT MATERIAL IDENTFICATION N  CORRECT MATERIAL IDENTFICATION N  CORRECT MATERIAL IDENTFICATION N  CORRECT MATERIAL REQUIRE N  ENGINEERING SIGN OFF Y (N)  DOES THIS MATERIAL REQUIRE AN  EXTRUSION REPORT Y (N)  CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK.  RECORD RESULTS BELOW  HRC HRB DUR A DUR D WEBSTI  SIZE OF TEST SAMPLE  HARDNESS / DUROMETER READING  LESTERS located in the Quality Office	- N						TOIZE NEOL		
SURFACE DAMAGE Y (N) CORRECT FINISH Y N CORROSION Y (N) CORRECT GRAIN DIRECTION Y N CORRECT MATERIAL PER M-DRAWING CORRECT THICKNESS PHOTO REQUIRED Y N CORRECT THICKNESS PHOTO REQUIRED Y N CORRECT MATERIAL IDENTFICATION CORRECT MATERIAL IDENTFICATION CORRECT MH ON THE MATERIAL DOES THIS MATERIAL REQUIRE ENGINEERING SIGN OFF Y (N) DOES THIS REQUIRE AN EXTRUSION REPORT Y (N)  CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK. RECORD RESULTS BELOW HRC HRB DUR A DUR D WEBSTI  WESTER SOCIETATION OF THE MATERIAL BIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  WESTER SOCIETATION OF THE MATERIAL SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  WESTER SOCIETATION OF THE MATERIAL SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING		N	CR						
SURFACE DAMAGE  CORRECT FINISH  CORROSION  CORRECT GRAIN DIRECTION  CORRECT MATERIAL PER M-DRAWING  CORRECT THICKNESS  PHOTO REQUIRED  CORRECT REF # TO LINK CERT  CORRECT MATERIAL IDENTFICATION  CORRECT M# ON THE MATERIAL  DOES THIS MATERIAL REQUIRE ENGINEERING SIGN OFF  Y  DOES THIS REQUIRE AN EXTRUSION REPORT  CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK.  RECORD RESULTS BELOW  HRC  HRC  HRB  DUR A  DUR D  WEBSTI  TYPE OF MATERIAL  SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  testers located in the Quality Office	DESCRIPTION	(Cr	neck				COMMEN	TS	
CORRECT FINISH CORROSION CORRECT GRAIN DIRECTION V N CORRECT MATERIAL PER M-DRAWING PHOTO REQUIRED CORRECT THICKNESS V N PHOTO REQUIRED V N CORRECT MATERIAL IDENTFICATION N CORRECT MATERIAL IDENTFICATION N CORRECT MATERIAL REQUIRE ENGINEERING SIGN OFF DOES THIS MATERIAL REQUIRE ENGINEERING SIGN OFF CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK. RECORD RESULTS BELOW HRC HRC HRB DUR A DUR D WEBSTI		Y	N)						
CORRECT FINISH CORROSION CORRECT GRAIN DIRECTION V N CORRECT MATERIAL PER M-DRAWING PHOTO REQUIRED CORRECT THICKNESS V N PHOTO REQUIRED V N CORRECT MATERIAL IDENTFICATION N CORRECT MATERIAL IDENTFICATION N CORRECT MATERIAL REQUIRE ENGINEERING SIGN OFF DOES THIS MATERIAL REQUIRE ENGINEERING SIGN OFF CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK. RECORD RESULTS BELOW HRC HRC HRB DUR A DUR D WEBSTI	SURFACE DAMAGE	Y	(N)						
CORRECT GRAIN DIRECTION  CORRECT MATERIAL PER M-DRAWING  CORRECT THICKNESS  PHOTO REQUIRED  Y  N  CORRECT R# TO LINK CERT  CORRECT MATERIAL IDENTFICATION  N  CORRECT M# ON THE MATERIAL  TO DOES THIS MATERIAL REQUIRE  ENGINEERING SIGN OFF  Y  DOES THIS REQUIRE AN  EXTRUSION REPORT  CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK.  RECORD RESULTS BELOW  HRC  HRC  HRB  DUR A  DUR D  WEBSTI  WESTER BOCATED IN THE QUAILITY OFFICE	CORRECT FINISH								
CORRECT MATERIAL PER M-DRAWING  CORRECT THICKNESS PHOTO REQUIRED CORRECT REF # TO LINK CERT CORRECT MATERIAL IDENTFICATION N CORRECT MATERIAL IDENTFICATION N CORRECT MATERIAL REQUIRE ENGINEERING SIGN OFF Y DOES THIS REQUIRE AN EXTRUSION REPORT Y  CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK. RECORD RESULTS BELOW HRC HRB DUR A DUR D WEBSTI SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  Lesters located in the Quality Office	CORROSION	Y	(1)						
CORRECT THICKNESS PHOTO REQUIRED Y N PHOTO REQUIRED Y N CORRECT MATERIAL IDENTFICATION N CORRECT MATERIAL IDENTFICATION N CORRECT MATERIAL REQUIRE ENGINEERING SIGN OFF Y DOES THIS MATERIAL REQUIRE ENGINEERING SIGN OFF Y DOES THIS REQUIRE AN EXTRUSION REPORT Y N  CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK. RECORD RESULTS BELOW HRC HRB DUR A DUR D WEBSTI SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  testers located in the Quality Office	CORRECT GRAIN DIRECTION	_	N						
PHOTO REQUIRED  CORRECT REF # TO LINK CERT  N  N  CORRECT MATERIAL IDENTFICATION  N  CORRECT M# ON THE MATERIAL  TO N  DOES THIS MATERIAL REQUIRE ENGINEERING SIGN OFF Y  DOES THIS REQUIRE AN EXTRUSION REPORT  CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK. RECORD RESULTS BELOW  HRC  HRC  HRB  DUR A  DUR D  WEBSTI  SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  Lesters located in the Quality Office			_	ASTM	B16				
CORRECT REF # TO LINK CERT  N PODULIS CORRECT MATERIAL IDENTFICATION N N CORRECT MATERIAL IDENTFICATION N N CORRECT M# ON THE MATERIAL N N N N N N N N N N N N N N N N N N N		_							
CORRECT MATERIAL IDENTFICATION N CORRECT M# ON THE MATERIAL N DOES THIS MATERIAL REQUIRE ENGINEERING SIGN OFF Y DOES THIS REQUIRE AN EXTRUSION REPORT Y  CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK. RECORD RESULTS BELOW  HRC HRB DUR A DUR D WEBSTI  TYPE OF MATERIAL  SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  testers located in the Quality Office			_						
CORRECT M# ON THE MATERIAL (Y) N  DOES THIS MATERIAL REQUIRE ENGINEERING SIGN OFF Y (N)  DOES THIS REQUIRE AN EXTRUSION REPORT Y (N)  CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK. RECORD RESULTS BELOW  HRC HRB DUR A DUR D WEBSTI  TYPE OF MATERIAL  SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  testers located in the Quality Office			_	80041115					
DOES THIS MATERIAL REQUIRE ENGINEERING SIGN OFF Y DOES THIS REQUIRE AN EXTRUSION REPORT Y N  CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK. RECORD RESULTS BELOW HRC HRB DUR A DUR D WEBSTI SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  testers located in the Quality Office			-						
ENGINEERING SIGN OFF Y N  DOES THIS REQUIRE AN EXTRUSION REPORT Y N  CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK.  RECORD RESULTS BELOW  HRC HRB DUR A DUR D WEBSTI  SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  testers located in the Quality Office		Y	N						
DOES THIS REQUIRE AN EXTRUSION REPORT Y N  CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK. RECORD RESULTS BELOW  HRC HRB DUR A DUR D WEBSTI SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  testers located in the Quality Office		V	(A)						
CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK.  RECORD RESULTS BELOW  HRC HRB DUR A DUR D WEBSTI  SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  Lesters located in the Quality Office		T	(A)			-			
CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK.  RECORD RESULTS BELOW  HRC HRB DUR A DUR D WEBSTI  SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  testers located in the Quality Office		V	M						
RECORD RESULTS BELOW  HRC HRB DUR A DUR D WEBSTI  SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  testers located in the Quality Office	EXTROGION REFORM	-	(14)						
RECORD RESULTS BELOW  HRC HRB DUR A DUR D WEBSTI  SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  testers located in the Quality Office									
TYPE OF MATERIAL  SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  testers located in the Quality Office	CUT SAMPLE PIECE						A HARDNE	SS CHECK.	
TYPE OF MATERIAL  SIZE OF TEST SAMPLE  HARDNESS / DUROMETER READING  testers located in the Quality Office							5115	5.1.5	
SIZE OF TEST SAMPLE HARDNESS / DUROMETER READING  testers located in the Quality Office	TYPE OF MATERIAL			HRC	HKE	-	DURA	DUR D	WEBSTER
HARDNESS / DUROMETER READING  testers located in the Quality Office				-		_			
testers located in the Quality Office		ıG İ				-			-
		_	etore	located in th	o Oualin	Office			
DC 18 INSPECTION		16	31013	iocated iii tii	e Quality	Office			
DC 18 INSPECTION ENCINEEDING SIGNOFF (1)									
OC 18 INSPECTION ENCINEEDING SIGNOFF (1)									
OC 18 INSPECTION ENGINEERING SIGNOFF (1)									
QC 18 INSPECTION ENGINEERING SIGNOFF (if requir	QC 18 INSPECTION						ENGINEER	ING SIGNOR	FF (if required)
A	INSPECTED BY: AT					SIGNI			
INSPECTED BY: SIGNED OFF BY:	14					SIGINE	OFF BY:		
DATE: /8/09/25 DATE:	DATE: /8/09/25						DATE:		

Attach this inspection sheet with the corresponding material cert and remit to be scanned and received in